

	SPECIFICATION OF GEAR REDUCER	Document No.	
		RS No.	01000-038
		Order No.	
		Designer	Hong.W.Ch.

CUSTOMER	ITEM No.
MODEL RPH 3HP 4P 1/10	QUANTITY

DRIVEN MACHINE				DRIVER			
Application				Kinds	E.Motor	Engine	Others
No. of rev.	(NOMINAL)	172.0	rpm	Power	3	KW	HP
Installation		Indoor	Outdoor	Type	TEFC	Poles	4
Impact load		Uniform	Medium	Heavy	Phase	Single	3
Ambient temp.		MAX.	40	Cycle	60	Hz	V
Allowable torque			kg m	Speed	1720		rpm
Operating time		hour per day					
Load peak per hour		below5	5~10	over 10			

SPECIFICATION OF REDUCER													
Nominal Ratio				1/10				MATERIAL & HEAT TREATMENT					
Service factor								Pinion		SCM415		HC	
Power cal.		Niemann		AGMA		BS		Gear		SCM415		HC	
Additional cooling		No		Water		Fan		Internal Gear					
				Lubricant				Worm					
Kinds				GREASE				Worm wheel					
Quantity		0.3				kg		Casing		GC200			
Viscosity		EP GREASE R00						Shaft(L.S)		SM45C			
Method		Oil bath		Forced				Symbol	HC:Carburizing		HF:High Frequency		
Max. oil temp.		120							HN:Nitriding		QT:Quenching-Tempering		
DIRECTION OF REV.(View from shaft side)								APPENDED DRAWINGS					

ACCESSORIES				WEIGHT (APPROX.)			
				Driver			kg
				Gear Reducer			kg
				Others			kg
				Total	56		kg

REMARKS	Except details specified on this DATA SHEET, all subjects including test						
	shall be performed in accordance with MAKER STANDARD.						
	*** PLEASE REFER TO APPENDED DWG. FOR THE FOLLOWING No. :						