

	SPECIFICATION OF GEAR REDUCER		Document No.	
			RS No.	01000-054
			Order No.	
			Designer	Hong.W.Ch.

CUSTOMER	ITEM No.
MODEL RPH 5HP 4P 1/30	QUANTITY

DRIVEN MACHINE				DRIVER			
Application				Kinds	E.Motor	Engine	Others
No. of rev.	(NOMINAL)	57.7	rpm	Power	5	KW	HP
Installation Indoor Outdoor				Type	TEFC	Poles	4
Impact load Uniform Medium Heavy				Phase	Single 3	Ins. class	F
Ambient temp. MAX. 40				Cycle	60 Hz	Voltage	V
Allowable torque kg m				Speed	1730		rpm
Operating time hour per day							
Load peak per hour below5 5~10 over 10							

SPECIFICATION OF REDUCER													
Nominal Ratio				1/30				MATERIAL & HEAT TREATMENT					
Service factor								Pinion		SCM415		HC	
Power cal.		Niemann		AGMA		BS		Gear		SCM415		HC	
Additional cooling		No		Water		Fan		Internal Gear					
				Lubricant				Worm					
Kinds		GREASE						Worm wheel					
Quantity		0.6				kg		Casing		GC200			
Viscosity		EP GREASE R00						Shaft(L.S)		SM45C			
Method		Oil bath		Forced				Symbol		HC:Carburizing HF:High Frequency			
Max. oil temp.		120				HN:Nitriding QT:Quenching-Tempering							
DIRECTION OF REV.(View from shaft side)								APPENDED DRAWINGS					

DIRECTION OF REV.(View from shaft side)			APPENDED DRAWINGS	
High speed shaft	CW	CCW	Outline dwg. No.	GKEN251
Low speed shaft	CW	CCW	Sectional dwg No.	
Arrangement of shaft			Painting (Munsell No.)	7.5BG 5/2

ACCESSORIES				WEIGHT (APPROX.)			
				Driver	kg		
				Gear Reducer	kg		
				Others	kg		
				Total	75	kg	

REMARKS	Except details specified on this DATA SHEET, all subjects including test						
	shall be performed in accordance with MAKER STANDARD.						
	*** PLEASE REFER TO APPENDED DWG. FOR THE FOLLOWING No. :						