


| | | | |
|---|----------------------------------|--------------|------------|
|  | SPECIFICATION OF GEAR REDUCER | Document No. | |
| | | RS No. | 01000-057 |
| | | Order No. | |
| | | Designer | Hong.W.Ch. |

| | |
|-----------------------|----------|
| CUSTOMER | ITEM No. |
| MODEL RPH 5HP 4P 1/50 | QUANTITY |

| DRIVEN MACHINE | | | | DRIVER | | | |
|--------------------|-----------|--------------|---------|---------|---------|--------|--------|
| Application | | | | Kinds | E.Motor | Engine | Others |
| No. of rev. | (NOMINAL) | 34.6 | rpm | Power | 5 | KW | HP |
| Installation | | Indoor | Outdoor | Type | TEFC | Poles | 4 |
| Impact load | | Uniform | Medium | Heavy | Phase | Single | 3 |
| Ambient temp. | | MAX. | 40 | Cycle | 60 | Hz | V |
| Allowable torque | | | kg m | Speed | 1730 | | rpm |
| Operating time | | hour per day | | | | | |
| Load peak per hour | | below5 | 5~10 | over 10 | | | |

| SPECIFICATION OF REDUCER | | | | | | |
|---|---------------|--------|-------|-------------------|---------------------------|-------------------------------------|
| Nominal Ratio | | | 1/50 | | MATERIAL & HEAT TREATMENT | |
| Service factor | | | | | Pinion | SCM415 HC |
| Power cal. | Niemann | AGMA | BS | | Gear | SCM415 HC |
| Additional cooling | | No | Water | Fan | Internal Gear | |
| Lubricant | | | | Worm | | |
| Kinds | | GREASE | | | Worm wheel | |
| Quantity | 1.2 | | | kg | Casing | GC200 |
| Viscosity | EP GREASE R00 | | | | Shaft(L.S) | SM45C |
| Method | Oil bath | Forced | | | Symbol | HC:Carburizing HF:High Frequency |
| Max. oil temp. | 120 | | | | | HN:Nitriding QT:Quenching-Tempering |
| DIRECTION OF REV.(View from shaft side) | | | | APPENDED DRAWINGS | | |

| | | | | | | | |
|----------------------|--|----|-----|------------------------|--|-----------|--|
| High speed shaft | | CW | CCW | APPENDED DRAWINGS | | | |
| Low speed shaft | | CW | CCW | Outline dwg. No. | | GKEN252 | |
| Arrangement of shaft | | | | Sectional dwg No. | | | |
| | | | | Painting (Munsell No.) | | 7.5BG 5/2 | |

| ACCESSORIES | | | | WEIGHT (APPROX.) | | | |
|-------------|--|--|--|------------------|--|----|----|
| | | | | Driver | | kg | |
| | | | | Gear Reducer | | kg | |
| | | | | Others | | kg | |
| | | | | Total | | 80 | kg |

| | | | | | | | |
|---------|--|--|--|--|--|--|--|
| REMARKS | Except details specified on this DATA SHEET, all subjects including test | | | | | | |
| | shall be performed in accordance with MAKER STANDARD. | | | | | | |
| | *** PLEASE REFER TO APPENDED DWG. FOR THE FOLLOWING No. : | | | | | | |