
#### HYOSUNG HEAVY INDUSTRIES

### SPEED - TORQUE & CURRENT CURVE

Curve No.

1ST\_E00004088

OUTPUT	225	kW	POLES	8	Р
VOLTAGE	-	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	246.2	kg∙m	FULL LOAD CURRENT	-	Α
LOCKED ROTOR TORQUE	90	%	LOCKED-ROTOR CURRENT	750	%
BREAKDOWN TORQUE	190	%	SPEED (at FULL LOAD)	890	r/min
GD <sup>2</sup> of LOAD :	-	$kg \cdot m^2$	GD <sup>2</sup> of MOTOR	79.797	kg·m²



NOTE 100% RATED VOLTAGE : SPEED-TORQUE CURVE AT : SPEED-TORQUE CURVE AT 90% RATED VOLTAGE : SPEED-TORQUE CURVE AT 80% RATED VOLTAGE D : SPEED-CURRENT CURVE AT 100% RATED VOLTAGE : SPEED-CURRENT CURVE AT RATED VOLTAGE 90% : SPEED-CURRENT CURVE AT 80% RATED VOLTAGE




## THERMAL LIMIT & TIME - CURRENT CURVE

Curve No.

1TL_E00004088
---------------

OUTPUT	225	kW	POLES	8	Р
VOLTAGE	-	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	246.2	kg·m	FULL LOAD CURRENT	-	Α
LOCKED ROTOR TORQUE	90	%	LOCKED-ROTOR CURRENT	750	%
BREAKDOWN TORQUE	190	%	SPEED (at FULL LOAD)	890	r/min
GD <sup>2</sup> of LOAD :	-	kg·m²	GD <sup>2</sup> of MOTOR	79.797	kg·m²




#### HYOSUNG HEAVY INDUSTRIES

# LOAD - POWER FACTOR & EFFICIENCY CURVE

Curve No.

1PE\_E00004088

OUTPUT	225	kW	POLES	8	Р
VOLTAGE	-	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	246.2	kg·m	FULL LOAD CURRENT	-	Α
LOCKED ROTOR TORQUE	90	%	LOCKED-ROTOR CURRENT	750	%
BREAKDOWN TORQUE	190	%	SPEED (at FULL LOAD)	890	r/min
GD <sup>2</sup> of LOAD :	-	kg·m²	GD <sup>2</sup> of MOTOR	79.797	kg·m²



NOTE

A : LOAD - POWER FACTOR CURVE

B : LOAD - EFFICIENCY CURVE