
HYOSUNG HEAVY INDUSTRIES


SPEED - TORQUE & CURRENT CURVE

Curve	No.
-------	-----

1ST_D1ML20602

OUTPUT	45	kW	POLES	6	Р
VOLTAGE	-	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	36.8	kg∙m	FULL LOAD CURRENT	-	Α
LOCKED ROTOR TORQUE	120	%	LOCKED-ROTOR CURRENT	670	%
BREAKDOWN TORQUE	270	%	SPEED (at FULL LOAD)	1190	r/min
GD ² of LOAD :	-	kg·m²	GD ² of MOTOR	4.492	kg·m²








THERMAL LIMIT & TIME - CURRENT CURVE

Curve No.

1TL_D1ML20602

OUTPUT	45	kW	POLES	6	Р
VOLTAGE	-	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	36.8	kg·m	FULL LOAD CURRENT	-	Α
LOCKED ROTOR TORQUE	120	%	LOCKED-ROTOR CURRENT	670	%
BREAKDOWN TORQUE	270	%	SPEED (at FULL LOAD)	1190	r/min
GD ² of LOAD :	-	$kg \cdot m^2$	GD ² of MOTOR	4.492	$kg \cdot m^2$




HYOSUNG HEAVY INDUSTRIES

LOAD - POWER FACTOR & EFFICIENCY CURVE

Curve No.

1PE_D1ML20602

OUTPUT	45	kW	POLES	6	Р
VOLTAGE	-	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	36.8	kg·m	FULL LOAD CURRENT	-	Α
LOCKED ROTOR TORQUE	120	%	LOCKED-ROTOR CURREI	NT 670	%
BREAKDOWN TORQUE	270	%	SPEED (at FULL LOAD)	1190	r/min
GD ² of LOAD :	-	$kg \cdot m^2$	GD ² of MOTOR	4.492	kg·m²



NOTE

A : LOAD - POWER FACTOR CURVE

B : LOAD - EFFICIENCY CURVE