
HYOSUNG HEAVY INDUSTRIES

SPEED - TORQUE & CURRENT CURVE

Curve No.

1ST_D1ML20606

OUTPUT	110	kW	POLES	6	Р
VOLTAGE	-	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	89.7	kg∙m	FULL LOAD CURRENT	-	Α
LOCKED ROTOR TORQUE	120	%	LOCKED-ROTOR CURRENT	710	%
BREAKDOWN TORQUE	170	%	SPEED (at FULL LOAD)	1195	r/min
GD ² of LOAD :	-	kg·m²	GD ² of MOTOR	17.034	kg·m²



NOTE 100% RATED VOLTAGE : SPEED-TORQUE CURVE AT : SPEED-TORQUE CURVE AT 90% RATED VOLTAGE : SPEED-TORQUE CURVE AT 80% RATED VOLTAGE D : SPEED-CURRENT CURVE AT 100% RATED VOLTAGE : SPEED-CURRENT CURVE AT RATED VOLTAGE 90% : SPEED-CURRENT CURVE AT 80% RATED VOLTAGE




THERMAL LIMIT & TIME - CURRENT CURVE

Curve No.

1TL_D1ML20606

OUTPUT	110	kW	POLES	6	Р
VOLTAGE	-	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	89.7	kg·m	FULL LOAD CURRENT	-	Α
LOCKED ROTOR TORQUE	120	%	LOCKED-ROTOR CURRENT	710	%
BREAKDOWN TORQUE	170	%	SPEED (at FULL LOAD)	1195	r/min
GD ² of LOAD :	-	$kg \cdot m^2$	GD ² of MOTOR	17.034	kg·m²




HYOSUNG HEAVY INDUSTRIES

LOAD - POWER FACTOR & EFFICIENCY CURVE

Curve No.

1PE_D1ML20606

OUTPUT	110	kW	POLES	6	Р
VOLTAGE	-	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	89.7	kg∙m	FULL LOAD CURRENT	-	Α
LOCKED ROTOR TORQUE	120	%	LOCKED-ROTOR CURRENT	710	%
BREAKDOWN TORQUE	170	%	SPEED (at FULL LOAD)	1195	r/min
GD ² of LOAD :	-	$kg \cdot m^2$	GD^2 of MOTOR	17.034	$kg \cdot m^2$



NOTE

A : LOAD - POWER FACTOR CURVE

B : LOAD - EFFICIENCY CURVE