
HYOSUNG HEAVY INDUSTRIES

SPEED - TORQUE & CURRENT CURVE

Curve	No.
-------	-----

1ST_E00004048

OUTPUT	150	kW	POLES	2	Р
VOLTAGE	-	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	40.8	kg∙m	FULL LOAD CURRENT	-	Α
LOCKED ROTOR TORQUE	150	%	LOCKED-ROTOR CURRENT	720	%
BREAKDOWN TORQUE	250	%	SPEED (at FULL LOAD)	3580	r/min
GD ² of LOAD :	-	$kg \cdot m^2$	GD ² of MOTOR	6.473	kg·m²



NOTE 100% RATED VOLTAGE : SPEED-TORQUE CURVE AT : SPEED-TORQUE CURVE AT 90% RATED VOLTAGE : SPEED-TORQUE CURVE AT 80% RATED VOLTAGE D : SPEED-CURRENT CURVE AT 100% RATED VOLTAGE : SPEED-CURRENT CURVE AT 90% RATED VOLTAGE : SPEED-CURRENT CURVE AT 80% RATED VOLTAGE




THERMAL LIMIT & TIME - CURRENT CURVE

Curve No.

1TL_E00004048

OUTPUT	150	kW	POLES	2	Р
VOLTAGE	-	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	40.8	kg∙m	FULL LOAD CURRENT	-	Α
LOCKED ROTOR TORQUE	150	%	LOCKED-ROTOR CURRENT	720	%
BREAKDOWN TORQUE	250	%	SPEED (at FULL LOAD)	3580	r/min
GD ² of LOAD :	-	$kg \cdot m^2$	GD ² of MOTOR	6.473	kg·m²




HYOSUNG HEAVY INDUSTRIES

LOAD - POWER FACTOR & EFFICIENCY CURVE

Curve No.

1PE_E00004048

OUTPUT	150	kW	POLES	2	Р
VOLTAGE	-	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	40.8	kg∙m	FULL LOAD CURRENT	-	Α
LOCKED ROTOR TORQUE	150	%	LOCKED-ROTOR CURRENT	720	%
BREAKDOWN TORQUE	250	%	SPEED (at FULL LOAD)	3580	r/min
GD ² of LOAD :	-	$kg \cdot m^2$	GD ² of MOTOR	6.473	kg·m²



NOTE

A : LOAD - POWER FACTOR CURVE

B : LOAD - EFFICIENCY CURVE