
HYOSUNG HEAVY INDUSTRIES

SPEED - TORQUE & CURRENT CURVE

Curve No.

1ST_E00004599

OUTPUT	225	kW	POLES	8	Р
VOLTAGE	-	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	246.24	kg·m	FULL LOAD CURRENT	-	Α
LOCKED ROTOR TORQUE	105	%	LOCKED-ROTOR CURRENT	750	%
BREAKDOWN TORQUE	200	%	SPEED (at FULL LOAD)	890	r/min
GD ² of LOAD :	-	kg·m²	GD ² of MOTOR	85.66	$kg \cdot m^2$



NOTE : SPEED-TORQUE CURVE AT 100% RATED VOLTAGE : SPEED-TORQUE CURVE AT 90% RATED VOLTAGE : SPEED-TORQUE CURVE AT 80% RATED VOLTAGE : SPEED-CURRENT CURVE AT 100% RATED VOLTAGE : SPEED-CURRENT CURVE AT 90% RATED VOLTAGE : SPEED-CURRENT CURVE AT 80% RATED VOLTAGE




THERMAL LIMIT & TIME - CURRENT CURVE

Curve No.

1TL_E00004599

OUTPUT	225	kW	POLES	8	Р
VOLTAGE	-	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	246.24	kg·m	FULL LOAD CURRENT	-	Α
LOCKED ROTOR TORQUE	105	%	LOCKED-ROTOR CURRENT	750	%
BREAKDOWN TORQUE	200	%	SPEED (at FULL LOAD)	890	r/min
CD^2 of LOAD.	_	ka.m²	CD ² of MOTOR	85 66	ka.m ²




HYOSUNG HEAVY INDUSTRIES

LOAD - POWER FACTOR & EFFICIENCY CURVE

Curve No.

1PE_E00004599

OUTPUT	225	kW	POLES	8	Р
VOLTAGE	-	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	246.24	kg∙m	FULL LOAD CURRENT	-	Α
LOCKED ROTOR TORQUE	105	%	LOCKED-ROTOR CURRENT	750	%
BREAKDOWN TORQUE	200	%	SPEED (at FULL LOAD)	890	r/min
GD ² of LOAD:	-	kg·m²	GD ² of MOTOR	85.66	kg·m²



NOTE

A : LOAD - POWER FACTOR CURVE

B : LOAD - EFFICIENCY CURVE