

HICO 3 PHASE INDUCTION MOTOR	PERFORMANCE DATASHEET	ISSUED	01/15/2026
		MODEL	25HP 4P

NAMEPLATE INFORMATION										
OUTPUT		RPM	VOLTS	Hz	FRAME SIZE	ENCLOSURE TYPE	S.F.	INS. CALSS	RATING	AMB. TEMP.
HP	kW									
25	18.5	1780	575	60	284TD	TEFC	1.25	F	CONT.	40°C
TEMP. RISE	NEMA DESIGN	kVA CODE	Class/Division Hazardous Location							
B	B	G	Class I, Division 2, Group B, C & D							

TYPICAL PERFORMANCE DATA						
EFFICIENCY (%)				POWER FACTOR (%)		
FULL LOAD		3/4 LOAD	1/2 LOAD	FULL LOAD	3/4 LOAD	1/2 LOAD
MIN.	NOM.					
92.4	93.6	93.7	93	81.4	76.8	66.5

CURRENT					
FULL LOAD AMPS	3/4 LOAD AMPS	1/2 LOAD AMPS	NO LOAD AMPS	STARTING CURRENT AMPS	STARTING CURRENT % FLC
24.6	19.5	15.1	11.4	155	630

TORQUE				ALLOWABLE STARTS PER HOUR	
FULL LOAD (lb-ft)	LOCKED ROTOR % FLT	BREAK DOWN % FLT	PULL UP % FLT	COLD	HOT
73.8	190	237	165	2	1

MECHANICAL DATA					
INERTIA			SOUND PRESSURE LEVEL @ 3 ft (dB(A))	PROTECTION GRADE	WEIGHT (Lbs)
ROTOR WR ² (lb-ft ²)	NEMA LOAD WK ² (lb-ft ²)	MAX ALLOWABLE WK ² (lb-ft ²)			
5.357	122	271	70	55	432

BEARING		GREASE	MOUNTING	
DE	ODE		TYPE OF CONSTRUCTION	TERMINAL BOX DESIGN
6312ZZ	6310ZZ	N/A	RIGID MOUNTING	NEMA


INVERTER DUTY DATA					
TYPE	HZ	HP	RPM	TORQUE(LB-FT)	NOTE
VARIABLE TORQUE	3~60	0.0031~25	90~1800	0.185~73.8	WITH TEMP. RISE CLASS F & S.F. 1.0
CONSTANT TORQUE	6~60	2.5~25	180~1800	73.8	
CONSTANT HP	60~90	25	1800~2700	73.8~49.2	

DRAWING NO.	ES1AS185710	REVISION	0.1
-------------	-------------	----------	-----

ALL DATA ABOVE ARE SUBJECTED TO CHANGE WITHOUT NOTICE.

HICO 3 PHASE INDUCTION MOTOR	SPEED - TORQUE & CURRENT CURVE				Curve No.
					1ST

OUTPUT	25	HP	POLES	4	P
VOLTAGE	575	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	73.8	lb-ft	FULL LOAD CURRENT	24.6	A
LOCKED ROTOR TORQUE	190	%	LOCKED-ROTOR CURRENT	630	%
BREAKDOWN TORQUE	237	%	SPEED (at FULL LOAD)	1780	RPM
GD ² of LOAD :	-	lb-ft ²	GD ² of MOTOR	5.357	lb-ft ²




NOTE

	A : SPEED-TORQUE CURVE AT	100% RATED VOLTAGE
	B : SPEED-TORQUE CURVE AT	90% RATED VOLTAGE
	C : SPEED-TORQUE CURVE AT	80% RATED VOLTAGE
	D : SPEED-CURRENT CURVE AT	100% RATED VOLTAGE
	E : SPEED-CURRENT CURVE AT	90% RATED VOLTAGE
	F : SPEED-CURRENT CURVE AT	80% RATED VOLTAGE

HICO 3 PHASE INDUCTION MOTOR	THERMAL LIMIT & TIME - CURRENT CURVE				Curve No.
					1TL

OUTPUT	25	HP	POLES	4	P
VOLTAGE	575	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	73.8	lb-ft	FULL LOAD CURRENT	24.6	A
LOCKED ROTOR TORQUE	190	%	LOCKED-ROTOR CURRENT	630	%
BREAKDOWN TORQUE	237	%	SPEED (at FULL LOAD)	1780	RPM
GD ² of LOAD :	-	lb-ft ²	GD ² of MOTOR	5.357	lb-ft ²




NOTE

- A : THERMAL LIMIT CURVE AT HOT CONDITION
- B : THERMAL LIMIT CURVE AT COLD CONDITION
- - - C : ※TIME-CURRENT CURVES(C,D,E) NEED BELOW DATA TO BE DRAWN
- ⋈ D : * LOAD GD2 AT MOTOR SHAFT
- ⋈ E : * SPEED-TORQUE CURVE OF LOAD

HICO 3 PHASE INDUCTION MOTOR	LOAD - POWER FACTOR & EFFICIENCY CURVE				Curve No.
					1PE

OUTPUT	25	HP	POLES	4	P
VOLTAGE	575	V	FREQUENCY	60	Hz
FULL LOAD TORQUE	73.8	lb-ft	FULL LOAD CURRENT	24.6	A
LOCKED ROTOR TORQUE	190	%	LOCKED-ROTOR CURRENT	630	%
BREAKDOWN TORQUE	237	%	SPEED (at FULL LOAD)	1780	RPM
GD ² of LOAD :	-	lb-ft ²	GD ² of MOTOR	5.357	lb-ft ²



NOTE

— A : LOAD - POWER FACTOR CURVE
- - - B : LOAD - EFFICIENCY CURVE



HICO

3 PHASE INDUCTION MOTOR

CONNECTION DIAGRAM

ISSUED

12/01/2024



ALL DATA ABOVE ARE SUBJECTED TO CHANGE WITHOUT NOTICE.